

STYLE-CASE

Beautiful, highly polished and ergonomic handheld enclosures

OKW presents the STYLE-CASE which has a high gloss surface finish, thus creating another design highlight for modern handheld control units. These elegant eye-catching plastic enclosures fit snugly in the hand and are easy and reliable to operate. The highly polished surface has a very pleasant feel which imparts a high quality and modern user experience.

- high-quality ASA with high UV protection or in PMMA material permeable to infra-red light (Plexiglas)
- glossy surface is easy to clean
- robust, offers protection up to IP 65, sealing kit available as accessory
- assembled by Torx drive stainless steel screws
- recessed operating panel for protecting the membrane keypad / product label
- integrated battery compartment: 2 x 1.5 V AAA (S, M) and 2 x 1.5 V AA (L), set of battery clips supplied as accessories
- attachment pillars for PCBs and components, self-tapping screws for mounting the boards are available as accessories



STYLE-CASE

Applications and Examples

- Ideal for design-oriented hand control units
- Many different types of remote control systems
- Specially made for the medical and social fields as well as in the household and in industry



Control unit for Relax and Massage Chairs



Mobile gas detector

View Customizing Options

What do you still need for your own very personal product? We can supply enclosures and tuning knobs with all necessary modifications for fitting your electronic components.
Customizing options for Style-Case



Machining



Lacquering



Printing




Laser marking



Decor foils



Special material



Installation / Assembly
of accessories

STYLE-CASE

Select Versions



B2802016
 STYLE-CASE S
 PMMA (IR) (UL 94 HB)
 black RAL 9005
 4.84"x1.89"x0.94"
 IP 40



B2802017
 STYLE-CASE S
 ASA (UL 94 HB)
 traffic white RAL 9016
 4.84"x1.89"x0.94"
 IP 40



B2803016
 STYLE-CASE M
 PMMA (IR) (UL 94 HB)
 black RAL 9005
 5.79"x2.20"x1.06"
 IP 65 opt., IP 40



B2803017
 STYLE-CASE M
 ASA (UL 94 HB)
 traffic white RAL 9016
 5.79"x2.20"x1.06"
 IP 65 opt., IP 40



B2804016
 STYLE-CASE L
 PMMA (IR) (UL 94 HB)
 black RAL 9005
 6.54"x2.52"x1.22"
 IP 65 opt., IP 40



B2804017
 STYLE-CASE L
 ASA (UL 94 HB)
 traffic white RAL 9016
 6.54"x2.52"x1.22"
 IP 65 opt., IP 40



B2804027
 STYLE-CASE L
 ASA (UL 94 HB)
 traffic white RAL 9016
 6.54"x2.52"x1.22"
 IP 65 opt., IP 40

Accessory "battery"



A9190020
 Set of battery clips
 Steel
 nickel-plated




B2904210
 Set of battery clips
 Steel
 nickel-plated

STYLE-CASE


Accessory "protection"



A9199005
Strain relief
PA 6
volcano




B2902111
Sealing kit S
TPV 50A



B2903111
Sealing kit M
TPV 50A



B2904011
Sealing L
TPV 50A



B2904111
Sealing kit L
TPV 50A



C2353849
Flexible cable grommet Ø 5,3
black

Accessory "wall/holder"



B2902031
Adhesive foil S



B2902037
Holder S
ASA (UL 94 HB)
traffic white RAL 9016



B2902039
Holder S
ASA (UL 94 HB)
black RAL 9005



B2903031
Adhesive foil M



B2903037
Holder M
ASA (UL 94 HB)
traffic white RAL 9016



B2903039
Holder M
ASA (UL 94 HB)
black RAL 9005



B2904031
Adhesive foil L



B2904037
Holder L
ASA (UL 94 HB)
traffic white RAL 9016

STYLE-CASE



B2904039

Holder L
ASA (UL 94 HB)
black RAL 9005

Accessory "screws"



A0304031

Self-tapping screws 0.087" x
0.197" (PZ1)

Subject to technical modification without notice. © by OKW Gehäusesysteme, Buchen/Germany.